



# Fleck 5810-XTR2



## Features & Benefits

- Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant
- Continuous service flow rate of 36 GPM with a backwash of 28 GPM
- Backwash capability accommodates softener tanks up to 21" and filters up to 21" in diameter
- Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system
- Time-tested, hydraulically-balanced piston for service and regeneration
- Optical sensor for precision cycle positioning
- Soft water refill for a cleaner brine tank
- Designed with double backwash for reduced hardness leakage
- Diagnostics for historical valve performance
- Programming stored in memory and will not be lost due to power outages
- Time of day super capacitor backup for power loss
- Large color LCD touch screen display
- Programmable relay output
- Remote lockout and regen input
- Easy electronic programming
- Error alarm
- Assistance screen with dealer contact information
- Programmable assistance interval with alarm for service
- Master settings by category
- Intuitive navigation
- Field Programmer for quick configuration and diagnostic data download to PC via USB
- Password lockout screen for added security
- Vacation mode to save water when not in use
- Tested and Certified by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.
- Tested and Certified by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance

6085 Main St  
St Andrews, MB, R1A 4A4

Phone: 204.482.9176  
greg@bluebisonwater.com  
www.bluebisonwater.com

**Blue Bison Water**